

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**


**THIS PAGE BLANK (USPTO)**



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>H04N 7/00, 7/10, 7/14</b>		<b>A1</b>	(11) International Publication Number: <b>WO 97/47135</b>
			(43) International Publication Date: 11 December 1997 (11.12.97)
(21) International Application Number: <b>PCT/US97/09178</b>		(74) Agents: TAYLOR, Edwin, H. et al.; Blakely, Sokoloff, Taylor & Zafman LLP, 7th floor, 12400 Wilshire Boulevard, Los Angeles, CA 90025 (US).	
(22) International Filing Date: <b>4 June 1997 (04.06.97)</b>			
(30) Priority Data:		(81) Designated States: AL, AM, AT, AT (Utility model), AU (Petty patent), AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
60/019,351 6 June 1996 (06.06.96) US 60/020,580 26 June 1996 (26.06.96) US 60/024,435 22 August 1996 (22.08.96) US 60/024,436 22 August 1996 (22.08.96) US 60/024,452 27 August 1996 (27.08.96) US 08/866,707 30 May 1997 (30.05.97) US			
(71) Applicant: INTEL CORPORATION [US/US]; 2200 Mission College Boulevard, Santa Clara, CA 95052 (US).		Published With international search report.	
(72) Inventors: WILLIAMS, Christopher, D.; 687 Pau Hana Drive, Soquel, CA 95073 (US). GOLDSCHMIDT IKI, Jean, M.; 475 Milan Drive #107, San Jose, CA 95134 (US). SHAH-NAZAROFF, Anthony, A.; 779 Hilmar Street, Santa Clara, CA 95050 (US). WATTS, Earl, Michael; 305 Vineyard Town Center #252, Morgan Hill, CA 95037 (US). HACKSON, David, N.; 1503 Yukon Drive, Sunnyvale, CA 94087 (US). MOORE, Kenneth, A.; 97424 Hoyt Street, Fremont, CA 94539 (US).			

(54) Title: METHOD AND APPARATUS FOR AUTOMATICALLY DETERMINING AND DYNAMICALLY UPDATING USER PREFERENCES IN AN ENTERTAINMENT SYSTEM



## (57) Abstract

A method and apparatus for automatically determining and dynamically updating user preferences in an entertainment system is provided. In a first embodiment, an apparatus comprises a storage medium (616) to store user preference information corresponding to at least a subset of a plurality of entertainment system users and a processor agent (604). The processor agent (604), communicatively coupled to the storage medium, is operative to monitor user interaction with the entertainment system and to automatically detect which user of the plurality of entertainment system users is currently using the entertainment system.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

-1-

**METHOD AND APPARATUS FOR AUTOMATICALLY DETERMINING  
AND DYNAMICALLY UPDATING USER PREFERENCES IN AN  
ENTERTAINMENT SYSTEM**

**RELATED APPLICATIONS**

This non-provisional application claims priority to provisional application no. 60/019, 351 by Jean Goldschmidt, Earl Watts and Kathleen Lane, for a Programming Preferences Agent Specification filed on June 6, 1996; provisional application no. 60/024,435 filed on August 22, 1996, for a Television Viewing Behavior Monitor by Jean Goldschmidt, Tony Shah, Christopher Williams and Kathleen Lane; provisional application no. 60/024,436 entitled Entertainment System Which Customizes Its Configuration To A Particular User, filed on August 22, 1996; provisional application no. 60/024,452 entitled Television Personalization, filed on August 27, 1996, by Jean Goldschmidt, Tony Shah, Christopher Williams and Kathleen Lane; and provisional application no. 60/020,580 entitled Customized Television Schedule With Suggested Viewing List, filed on June 26, 1996, by Jean Goldschmidt and Michael Watts. Each of the foregoing provisional applications are commonly assigned to Intel Corporation of Santa Clara, California.

**BACKGROUND OF THE INVENTION**

1. **Field of the Invention**

The present invention relates to the field of entertainment systems and, in particular, to a method and apparatus for automatically determining and dynamically configuring user preferences in an entertainment system.

2. **Background Information**

Numerous advances have been made in recent years in the field of entertainment systems. For example, programming guides are now prevalent on many cable systems throughout the country. In one embodiment, these programming guides are offered on a particular channel within the cable broadcast,

-2-

and provide programming information for the next several hours. More advanced ones of these prior art systems may allow the user to interact with the program guide to manually select a particular program to record or view.

Another example of advances in entertainment systems has been the advent of parental control, wherein a person may "lock out" or require a password for channels that may be unsuitable for certain members of the family. Equally impressive advances have been made in audio devices, video recorders/playback devices, etc. A number of these devices allow a user to manually program the device to record a program given appropriate information regarding the program (channel, date, start time, end time, etc.). Other current systems allow a user to manually "add" and "erase" channels and thereby generate a preferred "channel surfing" order. For example, the user may erase channels 3 and 4 in order to pass directly from channel 2 to channel 5 when channel surfing. However, with these systems the channel surfing order must be manually programmed by a user and must be manually re-programmed by the next user if he or she desires a different order. That is to say, none of these prior art entertainment systems are capable of automatically determining which user is currently using the system and dynamically configuring the entertainment system in accordance with a user profile corresponding to the user.

Thus, a need exists for a method and apparatus for automatically determining and dynamically updating user preferences in an entertainment system.

SUMMARY OF THE INVENTION

In accordance with the teachings of the present invention, a method and apparatus for automatically determining and dynamically updating user preferences in an entertainment system is provided. In one embodiment of the present invention, an apparatus for use in an entertainment system is provided including a storage medium to store user preference information for at least a subset of a plurality of entertainment system users, and a processor agent. The processor agent, communicatively coupled to the storage medium, is operative to monitor user interaction with the entertainment system, and to automatically determine which user of the plurality of entertainment system users is currently using the entertainment system.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be described by way of exemplary embodiments, but not limitations, illustrated in the accompanying drawings in which like references denote similar elements, and in which:

**Figure 1** is a block diagram illustrating a number of components making up an entertainment system in which the present invention may be practiced;

**Figure 2** is a flow chart illustrating the steps followed in dynamically customizing system operating parameters corresponding to user preferences in accordance with one embodiment of the present invention;

**Figure 3** is a flow chart illustrating the steps followed in determining which user of a plurality of system users is currently using the system according to one embodiment of the present invention;

**Figure 4** is a flow chart illustrating the steps followed identifying programming information which might be of interest to a user according to one embodiment of the present invention;

**Figure 5** is a block diagram illustrating an example computer system incorporating the teachings of one embodiment of the present invention;

**Figure 6** is a block diagram illustrating the software elements according to one embodiment of the present invention;

**Figure 7** illustrates a user profile database according to one embodiment of the present invention; and

**Figure 8** illustrates a program database according to one embodiment of the present invention.



DETAILED DESCRIPTION

In the following description, for purposes of explanation, specific numbers, materials and configurations are set forth in order to provide a thorough understanding of the present invention. However, it will be apparent to one skilled in the art that the present invention may be practiced without the specific details. In other instances, well known features are omitted or simplified in order not to obscure the present invention. Furthermore, for ease of understanding, certain method steps are delineated as separate steps, however, these separately delineated steps should not be construed as necessarily order dependent in their performance.

Turning now to **Figure 1**, a block diagram is presented illustrating the system components of one example of an exemplary entertainment system in which the present invention may be practiced. As will be discussed in greater detail below system **100** includes system controller **104** which, in one embodiment, is configured to store user profile information which controller **104** develops for each of the users of system **100**. In addition, system controller **104** is configured to retrieve and store entertainment programming information available from a wide variety of sources. During operation of system **100**, system controller **104** automatically determines which user of a plurality of system users is currently using the system by comparing received inputs and current settings to at least a subset of the user profiles for at least a subset of the plurality of entertainment system users. Having determined which user of the plurality of system users is currently using the system, system controller **104** dynamically configures the operating parameters of system **100** in accordance with the user preference information of the user profile corresponding to the determined entertainment system user, and offers programming/entertainment suggestions, and a host of additional value added features to enhance the user's enjoyment of system **100**. In one embodiment, system controller **104** may be a computer system incorporated with the teachings of the present invention, as will be discussed in further detail below. In another embodiment, system controller **104** may be a "set-top" box endowed with the necessary processing power and incorporated with the teachings of the present invention. Regardless of the particular embodiment, system controller **104** may also be referred to as a "convergence system" designed to integrate the world of entertainment systems

-6-

and computing platforms to achieve the beneficial results discussed in greater detail below.

Although the present invention is described in the context of the exemplary embodiments presented in the figures, based on the descriptions to follow, those skilled in the art will appreciate that the present invention is not limited to these embodiments and may be practiced in a variety of alternate embodiments. Accordingly, the innovative features of the present invention may be practiced in a system of greater or lesser complexity than that of the system depicted in **Figure 1**.

As shown, **Figure 1** illustrates but one example of an entertainment system incorporated with the teachings of the present invention. In the illustrated embodiment, system **100** includes television/monitor **102**, video recorder/playback device **106**, digital video disk (DVD)<sup>1</sup> recorder/playback device **114**, audio/video tuner and amplifier **110**, audio playback/recorder device **122** and compact disk player **112**, all coupled to a common input/output (I/O) bus **108**. It is to be appreciated that the use of the common I/O bus **108** is for ease of explanation in the diagram only, and that a number of alternative means of routing input and output signals may be beneficially employed. For example, audio input and output could be routed with an appropriate number of independent audio "patch" cables, video signals may be routed with independent coaxial cable, and control signals may be routed along a two-wire serial line, or through infrared (IR) communication signals or radio frequency (RF) communication signals.

In addition, system **100** includes speaker system **116**, microphone **118**, video camera **120** and a wireless input/output control device **132**. In one embodiment, wireless I/O control device **132** is an entertainment system remote control unit which communicates with the components of system **100** through IR signals. In another embodiment, wireless I/O control device **132** may be a wireless keyboard and cursor positioning device that communicates with the components of system **100** through IR signals or RF signals. In yet another embodiment, wireless I/O control device **132** may be an I/R remote control device similar in appearance to a typical entertainment system remote control with the

---

<sup>1</sup>DVD is currently used as an acronym for digital video disk. However, it appears that the usage is being changed to digital versatile disk to reflect the ability of DVD technology to be used for data other than video.

-7-

added feature of a track-ball, which allows a user to position a cursor on a display of system **100**.

At the core of the system is system controller **104** incorporated with the features of the present invention, configured to control a wide variety of features associated with each of the system components. As depicted, system controller **104** is coupled to each of the system components, as necessary, through I/O bus **108**. In one embodiment, in addition to or in place of I/O bus **108**, system controller **104** may be configured with a wireless communications transmitter (or transceiver), which is capable of communicating with the system components via IR signals or RF signals **108'**. Regardless of the control medium, system controller **104** is configured to control each of the entertainment system components of system **100**, although it is understood that each of the components may be individually controlled with wireless I/O device **132**.

As illustrated in **Figure 1**, system **100** can be configured to receive programming input from a wide variety of sources. In one embodiment, for example, system **100** receives programming input from any or all of the following sources: cable broadcast **124**, satellite broadcast **126** (e.g., via a satellite dish), very high frequency (VHF) or ultra high frequency (UHF) radio frequency communication of the broadcast networks **134** (e.g., via an aerial antenna), and/or the telephone/computer network interface **128**. Further, it will be appreciated by one skilled in the art, that cable broadcast input **124**, satellite broadcast input **126** and VHF/UHF input **134** may beneficially receive input from digital broadcast programming and digital cable programming. In addition to programming input, system **100** is also configured with a number of general purpose control outputs **130** which may be configured to control any number of devices. In one embodiment, for example, as system controller **104** configures system **100** to display a movie, it may also dim the lights in the room to a predetermined level to further enhance the viewing environment. Control circuitry which allows a computer system to control, for example, lighting, thermostat settings, and other household appliances are well known in the art and thus will not be described further. In another embodiment, system controller **104** analyzes programming content and configures system **100** to take full advantage of the programming. For example, if a television show is being broadcast in surround sound, system controller **104** determines that program is offered in surround sound and configures system **100** to display the television show in surround sound. If the

-8-

next show televised on the network is not broadcast in surround sound, system controller **104** determines this and configures system **100** to display the television show in stereophonic or monophonic sound, as appropriate.

Except for the incorporated teachings of the present invention (to be more fully described below), system controller **104** is intended to represent a broad category of computer systems known in the art. An example of such a computer system is a desktop computer system equipped with a high performance microprocessor(s), such as the Pentium® processor, Pentium® Pro processor, or Pentium® II processor manufactured by and commonly available from Intel Corporation of Santa Clara, California, or the Alpha® processor manufactured by Digital Equipment Corporation of Manard, MA; a number of audio and video input and output peripherals/interfaces for receiving, digitizing and compressing audio and video signals are also known in the art. It is to be appreciated that the housing size and design for system controller **104** may be altered, allowing it to better visually fit into system **100**.

It is also to be appreciated that the several entertainment system components depicted in **Figure 1** can be beneficially combined. By way of example, system controller **104** could be integrated into television/monitor **102**, DVD **114**, or audio/video tuner and amplifier **110**.

Turning now to **Figures 2** through **4**, flow charts illustrating one embodiment of the method steps of the present invention for automatically determining which of a plurality of users is currently using the system, and automatically configuring the system in accordance with user preference information of the user profile is shown. For ease of explanation, and not limitation, the method of **Figures 2** through **4** will be developed in the context of an example implementation, wherein a user first begins using system **100**, step **202**. It is to be appreciated that system **100** provides a number of alternate means by which system **100** may be activated. In one embodiment, the user simply uses wireless I/O device **132** to begin watching television **102**. In one embodiment, the user is "surfing" the Internet via system controller **104** and a modem (not shown) coupled to telephone/network communications I/O **128**. Regardless of the means by which the user activates system **100**, system controller **104** determines which user of a plurality of known system users is currently using system **100**, step **204**. The method by which system controller **104** determines

which user of a plurality of users is currently using system **100** is described more fully below.

Having determined which user of a plurality of users is currently using system **100** in step **204**, system controller **104** dynamically configures system configuration settings of system **100** in accordance with the user preference information found in the user profile corresponding to the identified user. Referring to **Figure 7**, depicted therein is one example of user profile database **700**. In the illustrated embodiment of **Figure 7**, user profile database **700** contains information (user preference information) associated with each of the different media supported in system **100**. For example, in the illustrated embodiment of **Figure 7**, user profile database **700** includes user preference information related to a television/monitor, a personal computer and audio components. As depicted, for television/monitor **102**, user profile database **700** tracks user preferred channels, volume, program genre information, whether to block content information, and whether supplemental programming is requested with a particular channel. In the illustrated embodiment, for example, user profile database **700** includes a profile for the fictitious "Joe User". As illustrated, Joe User's favorite television channel is channel 2, which he enjoys viewing at a moderate volume; he prefers watching sports-type programming, no blocking is required, nor is any supplemental programming requested. With respect to channel 7, Joe enjoys watching movies available on this channel, at low volume, and he wishes to block violent movies. With respect to channel 11, Joe enjoys watching this station for its news coverage, at moderate volume, without the need for blocking, and Joe desires a "window" to be displayed on the television/monitor in which supplemental programming related to stock quotes are to be presented. In one embodiment, system controller **104** retrieves specific stock quotes customized to Joe's portfolio. In one implementation, system controller **104** retrieves the specific stock quotes from a predetermined world wide web site on the Internet via telephone/network interface **128**. In an alternate implementation, system controller **104** retrieves general stock quote information from one of the broadcast network television channels. One skilled in the art will appreciate that in one embodiment, user profile database **700** may be stored locally in a storage medium found in system controller **104**, while in alternate embodiments user profile database **700** may be stored remotely and accessed by

-10-

system controller **104** through one of the many input ports of system controller **104**.

By way of additional examples, user profile database **700** includes information indicating Joe User's preferred computer settings, including preferred types of Internet sites (e.g., Games, Sports, and Financial), as well as preferred software applications (e.g., a clock and a birthday reminder application). User profile database **700** also includes information indicating Joe User's preferred audio component settings, including preferred radio stations and corresponding music types, as well as preferred listening volumes. In addition, user profile information may be beneficially used to tailor advertising to the current user of the system **100**. In one embodiment, for example, as the programming information is made available to system controller **104**, a wide variety of advertising segments may be downloaded which conform to the user profiles stored in a particular entertainment system. Accordingly, if system controller **104** determines that a child is using entertainment system **100**, it may restrict the advertising to breakfast cereal's and toys, whereas if the current user is an adult system controller may promote advertising for automobiles and home appliances. In another embodiment, system controller **104** may develop a customized news program, actively accumulating news stories that are particularly relevant or of particular interest to the current system user from any of the plurality of programming sources identified above.

It is to be appreciated that a wide range of configurable options can be monitored and stored in user profile database **700**. In addition to those illustrated in **Figure 7**, additional user preferences which may be stored in user profile database **700** include video controls such as sharpness, contrast, and brightness, audio controls such as surround sound processing types (including Dolby™ Surround, Dolby™ Digital, Dolby™ Surround Pro Logic, Dolby™ 3 Stereo, and THX™), various surround sound processing modes (including both number of channels and type of sound environment to emulate, such as concert hall, rock concert, movie theater, etc.), stereophonic mode, monophonic mode, closed captioning on/off, and preferred display layouts (e.g., window sizes and locations). Additional preference information may also be stored in user profile database **700**, including top ten favorite shows, most frequently watched/listened to source(s), most frequently watched/listened to channel(s)/station(s) per source, typical watching/listening periods, favorite genre(s), favorite commercial(s),

-11-

favorite actor(s)/actress(es). For example, in one embodiment, system controller **104** determines which commercials a user favors by empirically recognizing which commercials get muted, or which commercials are interrupted (e.g., with a change of channel). In another embodiment, system controller **104** may determine which commercials are preferred by a particular user by eliciting feedback from the user whether the user liked the commercial, the commercial genre, etc. (e.g., through the use of an on screen prompt). In one embodiment, these configurable options for audio and video components are stored in user profile database **700** and referenced according to the media source of the signal (e.g., satellite broadcast). By way of example, the user's preferred video and audio settings may differ based on the source of a signal, such as the surround sound processing mode preferences of "concert hall" for one audio station, "rock concert" for a second audio station, and "movie theater" for one of the satellite channels.

In one embodiment of the present invention, user profile database **700** also stores default configuration options for each component. For example, a particular volume level, contrast setting, brightness setting, etc. for television/monitor **102** is stored and used by system controller **104** in the event different channel-specific preferences are not stored in user profile database **700**. By way of another example, a particular volume level and station setting for audio/video tuner and amplifier **110** is stored and used by system controller **104** in the event more specific preferences are not stored in user profile database **700**.

In one embodiment of the present invention, system controller **104** also provides a television schedule grid which displays the current channel selections for a predetermined period of time (e.g., the next two hours, week, or several weeks). The current program scheduling to be displayed is available from a programming database, as discussed in more detail below with reference to **Figure 8**. The display of this television schedule grid is a configurable option which can vary from user to user based on the user's preference. In one embodiment, the television schedule grid displays only those channels which user profile database **700** indicates the current user watches. Additionally, in one embodiment the ordering of the channels on the television schedule grid varies based on the user's preference. In this embodiment, user profile database **700** maintains a record of a users spends watching each television channel. Then, when system controller **104** receives a request to view the television schedule grid

-12-

(e.g., via the user's remote control) it displays the channels in the grid in the order of most frequently watched to least frequently watched. In an alternate embodiment, the television schedule grid displays the channels in the grid based on the genre of programming available during the displayed time period. For example, channel 2 may be Joe User's favorite channel, but if channel 8 is airing a football game while channel 2 is airing a documentary on the history of knitting (not high on the list of Joe User's genre preferences), system controller **104** will display channel 8 before channel 2.

In one embodiment of the present invention, selection of various programs can be made via the television schedule grid. In this embodiment, a user can select a particular portion of the grid by moving a cursor across the grid to a cell in the grid that contains the title of the program to be selected and then "clicking" the mouse button while the cursor is within the cell. System controller **104** can then ask the user whether the selected program is to be watched or recorded and display or record the program as requested by the user.

Returning to the example implementation of **Figure 2**, in parallel to configuring the system configuration of system **100** in step **206**, system controller **104** continuously monitors the user interaction with system **100** to update and refine the user preference information stored in user profile database **700** in step **210**. In particular, system controller **104** monitors and logs each of the user inputs received by the entertainment system (e.g., volume, color, supplemental programming, time logged on a particular web page, etc.) and updates the user preference information found in the appropriate records of the user profile.

It is to be appreciated that, in order to accurately monitor and log user inputs, system controller **104** needs to be made aware of the user inputs. In one embodiment, input signals (e.g., channel/station changes, volume changes, web page addresses, etc.) are input to system **100** via system controller **104**, which in turn forwards control signals to the appropriate components to perform the desired function. In an alternate embodiment, inputs could be provided to different components of system **100** directly without going through system controller **104**. In this embodiment, system controller **104** could receive control signals from the different components which identify the user inputs. Alternatively, in this embodiment system controller **104** could passively monitor wireless signals



-13-

provided to various components of system **100**, such as via wireless I/O device **132**, in order to identify user inputs.

Once system **100** has been configured in accordance with the user preference information found in user profile database **700**, system controller **104** scans the programming information found in a program database to identify programs which may be of particular interest to the user, based on the user profile, in step **208**. The method in which system controller **104** provides appropriate programming suggestions will be described in further detail below. In one embodiment, the program database is part of system controller **104**, and is updated periodically by accessing a remote server (not shown) via telephone/network communications **128** or via other mediums such as distributed diskettes or CD ROMs, a vertical blanking interval (VBI) of an analog video signal, or an additional data stream corresponding to a digital video signal (e.g., from a satellite system). In an alternate embodiment, the program database is located on a remote server (not shown), and system controller **104** accesses the remote server when necessary. One example of a program database, suitable for use in the present invention, is depicted in **Figure 8**. In the illustrated embodiment of **Figure 8**, program database **800** provides programming information corresponding to various media (cable, RF broadcast, satellite, audio programming, etc.), channels available in each medium, program time slots, and the genre of the program in each time slot. This information is then available for each day of the week (Monday-Sunday), and for each day of the month (1-31), as appropriate. For ease of explanation, program database **800** is depicted as a three-dimensional array, however, program database **800** could be implemented using any of a wide variety of conventional data structures.

It is to be appreciated that additional information (not shown) can also be stored for the various channels in program database **800**. This additional information includes the length of the program, a program description/synopsis, actors/actresses, director, date of first airing or release, program genre, channel call-sign, rating, critique, etc.

Returning now to **Figure 2**, having provided programming suggestions, as appropriate in step **208**, system controller **104** continues to monitor user interaction with system **100** until system controller **104** detects a new user, step **220**. In the illustrated embodiment, system controller **104** continues to monitor

user interaction with system 100 and determine whether a new user is detected until system 100 is turned off.

Figure 3 illustrates the steps followed by system controller 104 in determining which of a plurality of system users is currently using system 100, in accordance with one embodiment of the present invention. In particular, Figure 3 illustrates steps 204 and 220 of Figure 2 in more detail, in accordance with one embodiment of the present invention. As depicted, the method begins with system controller 104 monitoring user interaction with system 100 and checking current system settings, step 302. This monitored user information is stored in a behavior log, as discussed in more detail below. In step 304, system controller 104 compares the information contained in the behavior log as well as the current system settings with user preference information for at least a subset of the plurality of entertainment system users. In one embodiment, the plurality of user profiles are stored locally, in system 100, and the entire user profile is used to determine which user is using the entertainment system. In an alternate embodiment, system controller 104 may load into a memory a select subset of user preference information for a first subset of the plurality of entertainment system users, and, if a match is not found, loads a subset of user preference information from a subsequent subset of the plurality of entertainment system user profiles until a match is found. Information available on the known system users is contained in a user profile database (e.g., user profile database 700) which may reside locally within system 100, or may reside at remote location. In one implementation, system controller 104 uses only that information in the behavior log which has been stored since the later of system controller 104 last being turned on and system controller 104 last identifying a particular user. In step 306, system controller 104 identifies whether the information of the behavior log matches that of the data for any of the known system users. In one embodiment, system controller 104 calculates a user metric for the information in the behavior log and the current system settings as well as for each of the known system users. If there is greater than a predetermined probability that the information in the behavior log matches the user profile of one of the known users, system controller 104 determines that a match has been made and, in step 308, configures system 100 in accordance with the user preference information of the user profile database 700.

-15-

In one embodiment, the user metric takes into account the current settings in system **100** for each user configurable option as stored in user profile database **700**, such as television channel, current volume setting, current audio station, program genre, etc. It is to be appreciated that in order to identify some information, such as program genre, system controller **104** may need to access program database **800** of **Figure 8** to identify which program and thus the program genre of the television channel currently being viewed. In other embodiments, this supplemental information may be provided in the broadcast itself as intercast information, or in the VBI.

To generate the metric, in one embodiment of the present invention, each of the configurable options is given a different predetermined weight and the weighted values are added together. By way of example, the television channel being viewed may be given a higher weight than the volume of the channel. This sum of weighted values is compared to a predetermined value and, if the sum exceeds the predetermined value, then the system controller **104** considers a match to be found. In one embodiment, the predetermined weights are dynamic, allowing the weight for a particular option to change as the duration of that option remains unchanged. For example, the weight of the television channel being viewed may be much higher if the channel has remained unchanged for a few minutes, indicating that a user is actually watching that channel, rather than if the channel changes every few seconds, indicating that a user is simply "flipping" through channels. That is to say, the weight given to the different configurable options is determined empirically over time, allowing system controller **104** to improve the accuracy of its ability to quickly identify which user is currently using system **100**.

In one embodiment of the present invention, the user is prompted for verification of the match in step **306** by system controller **104**. For example, system controller **104** may provide a window on television/monitor **102** wherein a number of pictures of possible system users are displayed, wherein the first picture displayed is that which system controller **104** has identified as the most likely system user, requesting that the user affirmatively respond (e.g., via remote control or voice command) when their picture is displayed; or alternatively, system controller **104** may provide an audio prompt in the form of a question, e.g., "Is that you, Joe?". If the match is verified as being accurate, then system controller

-16-

**104** proceeds to configure the system in step **308**. Otherwise, system controller **104** returns to step **302** to continue monitoring user interaction with system **100**.

In one embodiment of the present invention, system controller **104** allows the users to initially "train" the system with specific user preferences. This training allows the users to initially select some, or all, of their preferences. In one implementation, this training is through a direct input of specific options such as preferred channels, volume settings, program genre, etc. In an alternate implementation, the training of the system is done indirectly via an on-screen questionnaire(s), wherein the user is asked to select from a list of program genre (science fiction, sports, documentaries, etc.) that the user enjoys watching. System controller **104** then translates the responses to the questionnaire(s) to different configuration options available in system **100**.

In one embodiment of the present invention, system controller **104** uses a pre-programmed default setting until a user match is found in step **304**. In an alternate embodiment, system controller **104** uses "conservative" (e.g., low volume settings, display only non-blocked television channels, etc.) user preference options stored in user profile database **700** until a user match is found. For example, if parental controls are selected to block out several channels for one user but not for the other users, system controller **104** uses those parent controls as the default preferences until a user match is found.

In alternate embodiments of the present invention, different mechanisms may be beneficially employed to identify the current user of system **100** other than that described above. For example, in one embodiment the user of system **100** speaks into a microphone of system **100** (e.g., to activate system **100**). System controller **104** compares the audio input from the user to pre-stored audio samples from the plurality of possible users and identifies which of the pre-stored samples is closest to the audio input to identify the user. One example of suitable audio recognition software is SpeakerKey, commonly available from ITT Industries of Fort Wayne, Indiana. Another suitable audio recognition development software is Speech Print ID, commonly available from Voice Print Systems of Dallas, Texas. In another alternate embodiment, a video image of the user of system **100** is scanned using one or more video cameras of system **100**. System controller **104** compares the scanned image of the user to pre-stored visual scans of the plurality of possible users and identifies which of the pre-scanned images is closest to the scanned image of the current user to identify the user. One example of suitable

-17-

video recognition software is True Face CyberWatch, commonly available from Miros Inc., of Wellesley, Massachusetts.

Having determined which user of a plurality of entertainment system users is currently using system **100**, system controller **104**, in one embodiment, presents the user with a number of programming suggestions which most closely align with the user profile of the particular user, step **208** of **Figure 2**. **Figure 4** illustrates the method steps followed by system controller **104** to identify programming which might be of particular interest to the user according to one embodiment of the present invention. System controller **104** first accesses a program database searching for keywords which match user profile preferences, step **400**. That is, in accordance with the teachings of the present invention, system controller **104** accesses a program database, such as program database **800**, and searches through the available program information for keywords that match genre information, for example, contained in the user profile of the current user. In the illustrated embodiment of **Figure 4**, having accessed program database **800**, system controller **104** determines from the available programming information all programs which match the user's preferences for programming genre as found in user profile database **700**. For example, if Joe User appears from his user profile to be a fan of the University of Michigan football team, system controller **104** searches through program database **800** for University of Michigan football games. If none are found, system controller **104** may preferably default to sporting events in general.

Having developed a list of programming suggestions in step **400**, system controller **104** prompts the system user, in an interactive pop-up window, with the list of programming suggestions, step **402**. The user may select one of the suggested programming options through, for example, wireless I/O device **132**, or elect to forego the suggestion and continue to watch the program on the current channel, step **404**. If the user selects one of the suggestions in the interactive pop-up window in step **404**, system controller **104** configures system **100** to allow user to view the chosen program, in accordance with the user profile, step **406**.

In one embodiment of the present invention, user profile database **700** also includes storage for user-defined requests. System controller **104** allows individual users to input requests for particular suggestions. These requests can be for specific titles of shows/movies or keywords, the request may include

-18-

wildcards (e.g., any shows with "star" in the title), and can also be negative (e.g., no shows with "star" in the title). Given a particular search request, system controller 104 searches the programming information each time it receives updated programming information (via an on-line service, diskette, etc. as discussed above), and prompts the user with the found program information in step 402. The user is then able to select viewing and/or recording of the program.

If, however, the user elects to forego the suggested programming in step 404, system controller 104 may then prompt the user with the option of recording one of the suggested programs in step 408. If the user elects to record one of the program suggestions, system controller 104 configures system 100 to record the program selection to any one of the available recording media. In one embodiment, for example, system controller 104 may configure video recorder/playback device 106 with the requisite information necessary (date, channel, start time, end time, etc.) to record the program on video tape. In an alternate embodiment, system controller 104 may record the program selection on a mass storage device which is part of system controller 104 itself (see, for example, Figure 5 below). If, however, the user elects to forego recording any of the program suggestions made in step 410, system controller simply continues to monitor and update user preferences, in accordance with Figure 2. Although presented in the context of a video broadcast, one skilled in the art will appreciate that the foregoing is equally applicable to each of the plurality of programming input described earlier.

In one embodiment of the present invention, system controller 104 repeats the steps of Figure 4 each time a new user is detected, thereby providing current programming suggestions to the new user, as discussed above with reference to Figure 2. In addition, in one embodiment of the present invention, system controller 104 also repeats the steps of Figure 4 periodically. This allows new suggestions to be provided to the user. In an alternate embodiment, system controller 104 may provide programming suggestions to a user well in advance (e.g., a couple of days or weeks), with options for issuing reminder prompts, to record the program, or to forego further prompts of the program. In another embodiment, rather than waiting for a prompt from the user, system controller 104 may automatically provide a customized programming guide tailored to the user profile of the current user.

-19-

Turning now to **Figure 5**, a block diagram is presented illustrating an example system controller incorporated with the teachings of the present invention. In one implementation, system controller **500** may be used as system controller **104** of **Figure 1**. In the illustrated embodiment, system controller **500** includes processor **502** and cache memory **504** coupled to each other as shown. Additionally, system controller **500** includes high performance input/output (I/O) bus **506** and standard I/O bus **508**, as shown. Host bridge **510** couples processor **502** to high performance I/O bus **506**, whereas I/O bus bridge **512** couples high performance I/O bus **506** to standard I/O bus **508**. Coupled to high performance I/O bus **506** are network/communication interface **524**, system memory **514**, audio/video interface board **530** and video memory **516**. In turn, display device **518** is coupled to video memory **516**. In one embodiment, display device **518** is television **102** of **Figure 1**. Coupled to standard I/O bus **508** are mass storage device **520** keyboard and pointing device **522**, and I/O ports **526**. As illustrated, wireless communications interface **528** is coupled to I/O port **526**. In one embodiment, wireless communications interface **528** is an IR transceiver for receiving IR signals from and sending IR signals to the components of system **100**. In one embodiment, wireless communications interface **528** is an RF transceiver for receiving RF signals from and sending RF signals to the components of system **100**.

In one embodiment of the system controller **500**, keyboard and pointing device are coupled to standard I/O bus **508** with a serial communication interface cable, while in alternate embodiments it may be communicatively coupled with an infrared (IR) interface or a radio-frequency (RF) interface.

With continued reference to **Figure 5**, elements **502-530** perform their conventional functions as known in the art. In particular, network/communication interface **524** is used to provide communication between system **500** and any of a wide range of conventional networks, such as Ethernet, token ring, the Internet, etc. Similarly, audio/video interface board **530** is used to receive broadcast communications from any of a wide range of conventional broadcast media such as RF broadcasts, satellite broadcasts, cable broadcasts, etc. Mass storage device **520** is used to provide permanent storage for the data and programming instructions to implement the above described functions, whereas system memory **514** is used to provide temporary storage for the data and programming instructions when executed by processor **502**. I/O ports **526** are one or more

-20-

serial and/or parallel communication ports used to provide communication between additional peripheral devices which may be coupled to hardware system 500. Collectively, the elements coupled of system controller 500 are intended to represent a broad category of hardware systems, including but not limited to general purpose computer systems based on the Pentium® processor, the Pentium® Pro processor, or the Pentium® II processor commonly available from Intel Corporation of Santa Clara, California.

It is to be appreciated that various components of system controller 500 may be re-arranged. For example, cache 504 may be on-chip with processor 502. Alternatively, cache 504 and processor 502 may be packed together as a "processor module", with processor 502 being referred to as the "processor core". Furthermore, mass storage device 520, keyboard and pointing device 522, and/or display device 518 and video memory 516 may not be included in system controller 500. Additionally, the peripheral devices shown coupled to standard I/O bus 508 may, in alternate embodiments, be coupled to high performance I/O bus 506; in addition, in some implementations only a single bus may exist with the components of system controller 500 being coupled to the single bus. Furthermore, additional components may be included in system controller 500, such as additional processors, storage devices, or memories.

In one embodiment, the innovative features of the present invention discussed above may be implemented as a series of software routines run by system controller 500 of Figure 5. These software routines run a plurality or series of instructions to be executed by a processor, such as processor 502 in system controller 500. Initially, the series of instructions are stored on a storage device, such as mass storage device 520. It is to be appreciated that the series of instruction may be stored on any conventional storage device, such as a diskette, CD ROM, magnetic tape, DVD, laser disk, ROM, flash memory, etc. It is also to be appreciated that the series of instruction need not be stored locally, and could be received from a remote storage device, such as a server on a network, via network/communication interface 524. The instructions are copied from the storage device, such as mass storage device 520, into system memory 214 and then accessed and executed by processor 502. In one embodiment, these software routines are written in the C++ programming language. It is to be appreciated, however, that these routines may be implemented in any of a wide variety of programming languages. In alternate embodiments, the present



invention may be implemented in discrete hardware or firmware. For example, an application specific integrated circuit (ASIC) could be programmed with the above described functions of the present invention.

Figure 6 is a block diagram illustrating the software elements according to one embodiment of the present invention. In particular software architecture 600 is shown comprising a system controller application 602, system control agent 604 with associated user profile database 616 and program information database 614, and an operating system 618 with associated drivers. In particular, system controller application 602 interfaces with system control agent 604 and provides the user interface for system controller 104 of Figure 1.

System control agent 604 includes user detection module 606, suggestion module 608, usage monitor 610 and customization module 612. As illustrated, system control agent 604 is coupled to and able to obtain information from user profile database 616, program information database 614, and behavior log 624. User detection module 606 performs the steps of determining which of a plurality of system users is currently using system 100 as described above. Suggestion module 608 performs the steps of identifying programming which might be of interest to a user as described above. Usage monitor 610 monitors the user inputs and current system settings and records the information in records of user profile database 616. Customization module 612 controls the setting of the various configurable options in accordance with the preferences of the identified user as discussed above.

Behavior log 624 is a storage for log information detailing the usage of system 100. In the illustrated embodiment, system control agent maintains records in behavior log 624 for each component of system 100 detailing, as appropriate, which channel/station was watched/listened to by which users during which time periods of each day. The time increments for the time periods may vary, reasonably ranging up to five minutes. Additionally, in the illustrated embodiment, system control agent 604 accesses programming database 614 to identify, for each time period recorded for a user in behavior log 624, which program was watched/listened to by the user. In alternate embodiments, additional information is also maintained in behavior log 624 by system control agent 604. This additional information can include which Intericast™ data, if any, was viewed, changes in volume such as decreases or muting, which programs were recorded, which programs were suggested by system controller 104 and

-22-

whether or not the suggested programs were watched, which web pages were accessed and both when and how long they were accessed, which links were taken from which web pages, etc.

Additionally, according to one embodiment of the present invention, system control agent 604 periodically transmits a copy of the behavior log to a remote server for data compilation purposes. In this embodiment, system control agent 604 can request demographic information from each user to be transmitted with the behavior log to allow for better analysis of the log information contained in the behavior log.

System control agent 604 also receives event input stream 622 which identifies the user inputs to the various components of system 100. As discussed above, these user inputs may be made directly to system control agent 604 by the user or the components of system 100, or may be received indirectly from wireless signals transmitted to the components of system 100 by the user.

Basic input/output system (BIOS) 620 provides an interface between operating system 618 and the various input/output (I/O) devices coupled to the hardware system. Operating system 618 is a software service which provides an interface between BIOS 620 and system control agent 604 as well as other software applications, if any, being executed by system controller 104. Operating system 618 provides an interface, such as a graphical user interface (GUI), between the user and the system controller. According to one embodiment of the present invention, operating system 618 is the Windows™ 95 operating system, available from Microsoft Corporation of Redmond, Washington. However, it is to be appreciated that the present invention may be used with any other conventional operating system, such as other versions of Microsoft Windows™ (for example, Windows™ 3.0, Windows™ 3.1, Windows™ NT, or Windows™ CE), Microsoft DOS, OS/2, available from International Business Machines Corporation of Armonk, New York, the Apple Macintosh Operating System, available from Apple Computer Incorporated of Cupertino, California, the NeXTSTEP® operating system available from Apple Computer Incorporated, or the UNIX operating system, available from Santa Cruz Operations of Santa Cruz, California.

In the discussions above, several examples of configurable options are given in describing the operation of the present invention. It is to be appreciated that these are only examples of the options which can be used with the present

invention and that a wide range of options for the components of **Figure 1** can be automatically configured in accordance with the present invention.

Also in the discussions above, several references are made to prompting a user for input. It is to be appreciated that alternate embodiments may not include these prompting and that system controller **104** of **Figure 1** can automatically perform various functions without prompting. By way of example, if system controller **104** identifies a particular program which may be of interest to a particular user, system controller **104** can record the program without prompting the user.

It is also to be appreciated that although the discussions above discuss taking various actions for the current system user, the present invention can also automatically take actions on behalf of users not currently using the system. By way of example, in one embodiment system controller **104** of **Figure 1** identifies a program(s) which may be of interest to a user(s) other than the current user and automatically records that program. Subsequently, the user for which the program was recorded can be notified of the recording the next time the user is using the system **100**.

In one embodiment of the present invention, various automatically configured options discussed above can be viewed and modified by users. In this embodiment, users are able to access their preferences on user profile database **700** of **Figure 7** and add to, subtract from, and/or modify their recorded preferences.

Thus, the present invention automatically determined and dynamically configures user preferences in an entertainment system. As discussed above, the present invention advantageously monitors the user and/or user inputs to automatically identify one of a plurality of different users of the entertainment system. In one embodiment, this monitoring is automatic and continuous, advantageously allowing the system to continually check for and identify new users of the system. Furthermore, after identifying the current user, the present invention advantageously configures various options in the entertainment system to the identified user in accordance with that user's preferences. Additionally, the present invention advantageously updates user profiles continually, allowing the present invention to automatically adjust to changing user preferences.

While the method and apparatus of the present invention has been described in terms of the above illustrated embodiments, those skilled in the art

-24-

will recognize that the invention is not limited to the embodiments so described. The present invention can be practiced with modification and alteration within the spirit and scope of the appended claims. For example, although depicted as separate components, any number of the components of system **100** may be incorporated into multipurpose devices (e.g., a television/monitor/video cassette recorder/playback device). Further, system controller **104** may well be incorporated into any of the system components, and may not include all of the elements of Figure 5, or may, alternatively, include additional elements. Accordingly, the description is to be regarded as illustrative instead of restrictive on the present invention.

Thus, a method and apparatus for automatically determining and dynamically updating user preferences in an entertainment system has been described.

CLAIMS

We claim:

1. An apparatus for use in an entertainment system, the apparatus comprising:  
a storage medium to store user preference information corresponding to at least a subset of a plurality of entertainment system users; and  
a processor agent, communicatively coupled to the storage medium, operative to monitor user interaction with the entertainment system, and operative to automatically detect which user of the plurality of entertainment system users is currently using the entertainment system.
2. The apparatus of claim 1, wherein the processor agent is operative to automatically detect which user of the plurality of entertainment system users is currently using the entertainment system based on user interaction with the entertainment system and the user preference information.
3. The apparatus of claim 1, wherein the processor agent is operative to determine which of the plurality of entertainment system users is currently using the entertainment system by monitoring user input and current entertainment system settings and comparing the user input and current entertainment system settings to the user profile information for the subset of entertainment system users.
4. The apparatus of claim 3, wherein the user input includes information associated with television program selection, web page selection, volume settings, and/or supplementary program information.
5. The apparatus of claim 1, further comprising a programming storage medium, communicatively coupled to the processor agent, to store programming information, and wherein the processor agent is operative to dynamically configure the entertainment system in accordance with the user preference information corresponding to the detected user.

-26-

6. The apparatus of claim 5, wherein the dynamic configuration includes providing an updated list of web sites which correspond to user preferences and available programming information.
7. The apparatus of claim 5, wherein the dynamic configuration includes providing the user with supplemental program information.
8. The apparatus of claim 5, wherein the processor agent is operative to suggest program options to the user corresponding to the program information and the user preference information for the detected user.
9. The apparatus of claim 1, wherein the processor agent is operative to continuously update a user profile of the detected user in response to user interaction with the entertainment system.
10. The apparatus of claim 10, wherein the user profile is stored locally within the apparatus.
11. The apparatus of claim 10, wherein the user profile is stored remotely.
12. The apparatus of claim 10, wherein the user profile includes television programming preferences.
13. The apparatus of claim 10, wherein the user profile includes Internet preferences.
14. The apparatus of claim 13, wherein the Internet preferences include preferred web sites.
15. The apparatus of claim 13, wherein the Internet preferences include web site genre information corresponding to the content type of information preferred by the user, wherein the processor agent is operative to use the web site genre information to facilitate an active search of the Internet to provide the user with a list of new web sites, not previously accessed by the user, which match the user profile.

-27-

16. The apparatus of claim 8, wherein the processor agent is operative to prompt the user with the option of recording a program when the user has selected another program option, and to communicate with an entertainment system component to record the program.

17. The apparatus of claim 1, wherein the processor agent is operative to provide a user interface through which the user can manipulate a user profile of the user.

18. An entertainment system, the entertainment system comprising:  
at least one entertainment system component providing programming received via at least one input;  
a storage medium to store user preference information corresponding to at least a subset of a plurality of entertainment system users; and  
a processor, communicatively coupled to the at least one entertainment system component, operative to monitor user interaction with the entertainment system, to automatically detect which user of the plurality of entertainment system users is currently using the entertainment system, and operative to dynamically adjust operating parameters for the entertainment system in response to the user preferences for the detected user.

19. The apparatus of claim 18, wherein the user preference information is obtained from at least one user profile.

20. The entertainment system of claim 19, wherein there exists a user profile for each of the plurality of entertainment system users.

21. The entertainment system of claim 19, wherein the processor agent is operative to update the user profile of the current entertainment system user with user preference information obtained while monitoring user interaction with the entertainment system.

-28-

22. A method for automatically detecting which user of a plurality of users is currently using an entertainment system, the method comprising the steps of:

- (a) monitoring the user's interaction with the entertainment system;
- (b) comparing the user's interaction with the entertainment system against stored user preferences; and
- (c) determining which user of the plurality of users is currently using the entertainment system, based on the result of said step of comparing.

23. The method of claim 22, wherein the step of monitoring comprises passively logging user definable settings to a temporary log.

24. The method of claim 23, wherein the user definable settings include channel and station information, volume information and supplementary programming information.

25. The method of claim 22, wherein the step of determining comprises calculating a metric of the likelihood that the information contained in the temporary log matches that of one of the plurality of system users for which preference information is available.

26. The method of claim 22, further comprising the step of:

- (d) configuring the entertainment system in accordance with the user preferences for the determined user.

27. The method of claim 26, wherein the step of configuring comprises the steps of:

- (d.1) accessing a database containing user preferences; and
- (d.2) adjusting operating parameters of the entertainment system in accordance with the user preferences corresponding to the user identified in step (c).

28. In an entertainment system including a system controller, a television/monitor, an audio input device and a video input device, a method for automatically configuring the entertainment system for an identified user of a plurality of system users, the method comprising the steps of:



-29-

- (a) determining which user from the plurality of system users is currently using the entertainment system;
- (b) retrieving user preference information corresponding to the identified user;
- (c) scanning programming information for available programming corresponding to user preference information; and
- (d) adjusting the entertainment system in accordance with the user preference information and available programming.

29. The method of claim 28, wherein the step of determining comprises the steps of:

- (a.1) prompting the user to speak into the audio input device, wherein the speech is recorded by the system controller;
- (a.2) comparing the speech input with a stored audio clip of each of the plurality of system users; and
- (a.3) identifying the user from the plurality of system users based on the comparison of recorded speech and audio clips.

30. The method of claim 28, wherein the step of determining comprises the steps of:

- (a.1) prompting the user to pose for the video input device, wherein an image of the user is recorded by the system controller;
- (a.2) comparing the recorded video image with a stored video image of each of the plurality of system users; and
- (a.3) identifying the user from the plurality of system users based on the comparison of recorded video image with the plurality of stored video images.




FIGURE 1

2/8




FIGURE 2

3/8




FIGURE 3

4/8





FIGURE 4



## FIGURE 5

6/8




FIGURE 6

700

USER NAME	TELEVISION				COMPUTER		AUDIO-COMPONENTS					
	CH	VOL	GENRE	BLOCK	SUPP-PROG	INTERNET	AUTO-FEATURE	STATIONS	TYPE	VOL	••	•••
JOE USER	2	0	S	NONE	NONE	GAMES	CLOCK	750KHZ	J	-	••	•••
	5	+	M	NONE	NONE	SPORTS	BIRTHDAY REMINDERS	800KHZ	P	•	•	•••
	7	-	M <sub>v</sub>	V <sup>++</sup>	NONE	FINANCIAL		1.2MHZ	R	•	•	•••
								1.195MHZ	J	•	•	•••
	11	0	N	NONE	Q	••	••	••	••	•	•	•••
•• ••	••	••	••	••	••	••	••	••	••	••	••	•••
	••	••	••	••	••	••	••	••	••	••	••	•••

KEY:	VOLUME:
S-SPORTS	"+"-HIGH
M-MUSIC	"0"-MEDIUM
M <sub>v</sub> -MOVIES	"-"-LOW
N-NEWS	
Q-QUOTES	
P-POP	
R-ROCK	
J-JAZZ	

FIGURE 7



MEDIUM		DAYS OF MONTH								DAYS OF WEEK		M-SU 1-31							
		CH	12AM	12:30A	1:00A			10:00P	10:30P	11:00P	11:30P								
CABLE		1	~~~~~	~~~~~	~~~~~	• • •	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~
		2	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~
		• • •	• • •	• • •	• • •	• • •	• • •	• • •	• • •	• • •	• • •	• • •	• • •	• • •	• • •	• • •	• • •	• • •	• • •
SATELLITE		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
AUDIO		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

FIGURE 8

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/US97/09178

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :H04N 7/00, 7/10, 7/10, 7/14

US CL :348/12, 13, 10, 7, 6

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 348/12, 13, 10, 7, 6

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS - user preferences, web page, web site, interactive, two-way, user id, user code,

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y,P	US 5,583,560 A (FLORIN et al) 10 December 1996, col. 2, lines 20-67, col. 3, lines 1-60, col. 9, lines 59-67, col. 10, lines 1-44, col. 11, lines 46-67, col 12., lines 1-58.	1-30
Y,P	US 5,550,575 A (WEST et al) 27 August 1996, col. 4, lines 48-67, col. 5, lines 1-52.	1, 2, 18, 22, 28
Y,P	US 5,572,643 A (JUDSON) 05 November 1996, col. 7, lines 6-17.	4, 6, 15

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A* document defining the general state of the art which is not considered to be part of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E* earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G* document member of the same patent family
*O* document referring to an oral disclosure, use, exhibition or other means	
*P* document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

04 AUGUST 1997

Date of mailing of the international search report

03 SEP 1997

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

B. Ravi  
Vivek Srivastava

Telephone No. (703) 305 - 4038